# **FJ FORSTHOFF**



## Hand-held welding torches QUICK-L

The easy to handle, lightweight and uncomplicated hot air welding torch for the tarpaulin processing firm.

### **Product description**

Modification of the reliable model Quick-L-Electronic. Instead of the infinitely variable temperature setting known from this device, the Quick-L is equipped with two fixed heating stages with additional cold stage.

As the welding of tarpaulins, tents and awnings is often only carried out with one type of material and in one welding width only, an uncomplicated device equipped with heating stages is best suited for the processing firm.

The device's heat output is adapted to the 20 mm or 40 mm wide slip-on nozzles required by the tarpaulin manufacturer.

- Heat output in conjunction with flat nozzle 20 mm: 900 W 230V
- Heat output in conjunction with flat nozzle 40 mm: 1500 W 230V

The motor's commutator carbons can be replaced several times, thus facilitating a continuous operation of the device. The carbons are easy to replace from the outside, without having to open the device.

New! Our hand-held welding torches' carbon brushes are equipped with a safety lock that prevents damage to the motor when the carbons are used up.

The tarpaulin welding device QUICK-L with versatile accessories to weld truck tarpaulins, tents and awning materials.

# **FJ FORSTHOFF**

### **Technical specifications**

Model	QUICK-L
Voltage	230 V 50/60 Hz or 120 V 50/60 Hz
Heat output	Depending on slip-on nozzle 900 W 230 V or 1500 W 120 V
Temperature	Switchable in two fixed heating stages
Weight	1200 g with 3 m connection cable
Dimensions	Length 320 mm, handle diameter 52 mm
Electrical safety	II / 🗖 (Double insulated)

### Areas of applications

- Car upholsterers
- Tarpaulin manufacturers
- Tent manufacturers
- Canvas covers
- Manufacturers of advertising tarpaulins

### Accessories





Item No. 4000 Round nozzle, 5 mm Nozzle, 20 mm flat



Item No. 4003 Nozzle, 40 mm flat Insulating tube



Item No. 2000

Item No. 2004

Item No. 2007

Heating element

Heating element

630 W

900 W

1500 Ŵ

Heating element

Item No. 7000 Pressure roller twoarmed, 45 mm

Item No. 6998 Pressure roller twoarmed, 45 mm, ball bearing mounted



Item No. 7001 Pressure roller onearmed, 45 mm

Item No. 6997 Pressure roller onearmed, 45 mm, ball bearing mounted



Item No. 7006 Pressure roller onearmed, 45 mm, 45° offset (patented)

Item No. 6995 Pressure roller onearmed, 45 mm, 45° offset (patented) ball bearing mounted



Item No. 7012 Metal case



Abbeon Cal, Inc. 1363 Donlon Street Unit 1 Ventura, CA 93003-8387

# armed, 80 mm, ball



Item No. 7002 Pressure roller two

armed, 80 mm Item No. 6996 Pressure roller two

bearing mounted